

# Powerful Compact Enterprise Server for Edge AI and Compute



## Supermicro SYS-E403-13E-FRN2T



### Enterprise Edge Server with Multiple GPUs for AI Inferencing

Supermicro's E403-13E-FRN2T is a high-performance powerhouse system engineered to deliver powerful computing capabilities in a compact form factor. Designed as a short-depth system, it expands the possibilities of what types of applications can be deployed at the enterprise edge, such as edge AI inferencing, real-time video analytics, and multi-access edge computing, helping bring data center-level performance closer to where the data is generated. It has been specifically designed for deployment flexibility to easily fit in an IT closet or placed in a wall-mount configuration for space limited locations.

The system uses 4th and 5th Gen Intel® Xeon® Scalable processors with up to 300W TDP with air-cooling. This makes it possible to have access to processing power that would typically be found in data center rack mount locations. Additionally, the E403-13E-FRN2T features three PCIe full-height/full-length slots enabling the deployment of one double-width GPU or two single-width GPUs for Edge AI inferencing. This flexibility makes it an excellent choice for demanding edge AI workloads and other compute-intensive tasks in constrained environments.

***Supermicro has a solution to deploy this system in an outdoor enclosure for harsh environments***

### Intel Products and Technologies

Accelerating AI and Analytics at the Edge



Intel® Xeon® Processors



Intel® Arc™ GPU



OpenVINO™ Toolkit




Intel® oneAPI Toolkit

# Key Features

Empowered by Intel.



Edge AI Ready



Three PCIe 5.0x16 Slots



Flexible Deployment



Remote Management

## Supermicro SYS-E3403-13E-FRN2T



## Product Specifications

|                                 |                                                                                                           |
|---------------------------------|-----------------------------------------------------------------------------------------------------------|
| CPU                             | Single Socket E (LGA-4677), 5th Gen Intel® Xeon® / 4th Gen Intel® Xeon® Scalable processors               |
| Graphics                        | Up to (1) double-width or (2) single-width GPUs                                                           |
| Memory                          | (8) DIMM slots, max memory (1DPC): Up to 2TB 5600MT/s ECC DDR5 RDIMM                                      |
| Storage                         | Total (4) bays. (2) front hot-swap 2.5" NVMe drive bays and (2) internal fixed 2.5" SATA* drive bays      |
| Wireless Network                | Available through an add-on module                                                                        |
| LAN                             | (1) RJ45 1 GbE Dedicated BMC LAN port and (2) RJ45 10 GbE LAN ports (Intel® Ethernet Controller X550-AT2) |
| Operating / Non-Operating Temp. | 32°F to 113°F/ -40°F to 158°F                                                                             |
| Dimension (W x D x H)           | 10.5" x 16" x 4.62"                                                                                       |
| Weight                          | 18.5 lbs (8.16 kg)                                                                                        |
| OS                              | Windows Server 2022, RHEL 9.2, Oracle Linux 9.2, Ubuntu 22.04                                             |

## Learn More

[Supermicro SYS-E3403-13E-FRN2T](#)